


Ambient Lite ____ Monitor

See the Unseen!




Ambient Lite

Our Ambient Lite Air Quality Monitor where your search stops if you are looking to quantify the concentration and impact of air toxin at an outdoor location. The user can accurately monitor all primary air pollutants and toxic gases simultaneously!

The monitor comes with **WiFi, RS-485 (MODBUS) / GSM (optional)** and Micro-SD card storage which enables the user access real-time and historic data through multiple devices via **AQI Mobile or Web Dashboard** anytime, anywhere

It provides real-time measurements of:



TVOC

Oxygen



Designed to be discreet

With a minimalistic design and aesthetical design, Smart outdoor is tailor-made for commercial, industrial, and research-based applications. It flexibly blends with any outdoor environment-Construction sites, Airpoets, Railways, Highways, Traffic junction and more.














Real-Time Air Quality Monitoring



WiFi, RS-485 or GSM (optional)



Detects Toxic Gases



Weather Station (optional)



AQI Cloud Storage



Battery (optional)



Micro SD Card Storage



Micro-USB cable

Salient Features


Technical **Specifications**

Product Name	Sensor Type	Range	Resolution	Accuracy
PM10, PM2.5 & PM1	90° Light Scattering	0 to 30,000µg/m³	1 μg/m³	0-150 μg/m³ is for ±10% & for 150 μg/m³ onwards is ±15%
Temperature	Digital Sensor	-40 to 70 °C	0.1°C	±5°C
Humidity	Digital Sensor	0 to 100% RH	1% RH	±3% RH
Carbon Dioxide (CO2)	NDIR	1 to 10,000ppm	1ppm	±3%
Nitrogen Dioxide (NO2)	Electrochemical	0 to 20ppm	1ppb	±3%
Carbon Monoxide (CO)	Electrochemical	0 to 1000ppm	10ppb	±3%
Sulphur Dioxide (SO ₂)	Electrochemical	0 to 100ppm	1ppb	±3%
Ozone (O3)	Electrochemical	0 to 20ppm	1ppb	±3%
Nitric Oxide (NO)	Electrochemical	0 to 20ppm	1ppb	±3%
TVOC	MOS	0 to 65ppm	10ppb	±3%
Hydrogen Sulphide (H2S)	Electrochemical	0 to 100ppm	1ppb	±3%
Noise	Noise	30-140dB	1dB	±3%
Methane (CH4)	PID	0 to 20ppm	0.1 %	±3%
Oxygen (O2)	Electrochemical	0 to 30%	1%	±3%

Product Specifications


Features	Descirption		
Connectivity	Wifi / RS-485(MODBUS)/ GSM (optional)		
Operating Temperature	-40°C to 70°C		
Storage Temperature	-30°C to 130°C		
Power Supply	12V DC		
Voltage	230V		
Data Accessibility	AQI mobile & smart TV app, and web-dashboard		
Storage	Micro SD Card Storage + Cloud Storage (with AQI Dashboard)		
Web Dashboard	Live web dashboard for remote data access		
Mobie App	AQI INDIA (availabe on ios and android)		
Battery	Optional		

Weight: 2kg (Approx)
Thickness: 14cm




Scan the QR Code


Monitor the air around you by scanning the AQI QR code anytime, anywhere.



Bar Graphs



Line Graphs



Weekly Summary



Line Graphs



Monthly Summary



2-Axis Comparison Chart



See what's in the air you breathe



Download the AQI App







AQ Mobile Application

Empowering you to make informed decisions with easy access to the data.



24*7 remote access to the monitored data



Empowering you to make informed decisions anytime, anywhere, with easy access to the data you need.

www.aqi.in



Insightful Air quality monitoring dashboard




Export recorded data anytime anywhere



Compare different air quality parameters of two or more location

Real-time, Historic, link generation, comparison, Tree view and a lot more features.









AQ TV Application

Empowering you to make informed decisions anytime, anywhere, with easy access to the data you need.





Choose from multiple

ranges of themes






Integrated and controlled via the AQI mobile app



Compare your indoor air quality with outdoor



Trusted By

We are honored to work with so many well-known market giants.





































THANK YOU THANG

THANK YOU THAN

THANK YOU THANK

THANK YOU THANG

Address

706, 7th floor, Crown heights, Rohini Sec-10, New delhi-110085, India

Phone

(+91) 73918-73918

Email

info@purelogic.in



To Know more

www.pranaair.com